

# Clock Synchronization for Wireless Sensors at the Physical Layer

Omid Abari, Hariharan Rahul and Dina Katabi

## Synchronized Wireless Sensors

Frequency synchronization opens many new opportunities:

- Data aggregation over the air
- Distributed Modulation
- Distributed Compressive Sensing over the air

Why are today's wireless sensors not synchronized?

Wireless nodes have different clocks with slightly different frequencies.

**AirShare transmits a reference clock over the air.**

### Challenge

Wireless nodes typically use a sine wave of 10-40 MHz for their reference clock.


**FCC forbids transmitting such a low-frequency signal for unlicensed use.**

## AirShare

Transmits two sine waves separated by the desired clock frequency.

Eg., for a clock of 10 MHz, send tones at 175 MHz and 185 MHz.


Each wireless node multiplies the received reference signal by itself and applies a band pass filter to extract the desired clock frequency.



$$(\cos(2\pi f_1 t) + \cos(2\pi f_2 t)) \cdot (\cos(2\pi f_1 t) + \cos(2\pi f_2 t)) =$$



$$\cos(2\pi(f_2 - f_1)t) + \cos(2\pi(f_2 + f_1)t) +$$

$$\frac{1}{2} \cos(2\pi(2f_1)t) + \frac{1}{2} \cos(2\pi(2f_2)t) + 1$$



## Microbenchmark Coherent Transmission



TX and RX nodes use the same reference clock that they receive over the wireless medium.



**AirShare reduces the CFO by 300-400 ×**

## Application 1 Distributed Rate Adaptation


Sensors transmit simultaneously and create distributed codes over the air.




**Throughput gains of 1.6-3 × over ZigBee for 6 sensors**

## Application 2 Over-the-air Function Computation

Sensors transmit coherently so that sink directly receives the desired function value.



**Many different functions: sum, mean, variance, max, min, median, etc.**



**Quadratic throughput gains**